

PVC PRESSURE HOSE



CHEMICAL / MULTIPURPOSE




SIMPSON - SPRAY HOSE

The Simpson Spray hose is constructed from high quality PVC compounds, the smooth inner tube and cover provide excellent kink resistance and flexibility. The clear inner tube is resistant to a wide range of agricultural and industrial pesticide and weedicide chemicals.

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
		MPa	psi		
10	16.2	2.0	300	20, 40#, 100, 300#	P-SSS-010-***
12.5	18.7	2.0	300	20, 30#, 100, 200#	P-SSS-012-***
19	28	1.6	230	20, 50, 100	P-SSS-020-***
25	34	1.6	230	20, 100	P-SSS-025-***

denotes the product is supplied on a plastic or wooden reel.

ILLAWARRA CLEAR MULTI-PURPOSE



Translucent dual purpose food contact / petrol hose. Meets AS/NZS 2070(Non Toxic food grade) Manufactured with a clear tube resistant to many oils and petroleum based products while conforming to the Australian Standard for food contact.

Temperature Range: -5°C - +60°C NOT SUITABLE FOR ETHANOL

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
		MPa	psi		
6	12	1.6	230	20, 50#, 100, 300#	P-SIL-006-***
8	14	1.6	230	20, 50#, 100, 300#	P-SIL-008-***
10	16	1.6	230	20, 40#, 100, 200#	P-SIL-010-***
12.5	18.5	1.6	230	20, 30#, 100, 200#	P-SIL-012-***
16	22	1.6	230	20#, 100	P-SIL-016-***
20	27	1.6	230	20, 100	P-SIL-020-***
25	33	1.4	200	20, 100	P-SIL-025-***
32	41	1.2	145	20, 60	P-SIL-032-***
38	49	1.2	145	20, 60	P-SIL-038-***
50	63	0.9	130	20, 40	P-SIL-050-***

denotes the product is supplied on a plastic or wooden reel.

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC PRESSURE HOSE



DRINKING / AIR BREATHING

FRANKLIN DRINKING WATER HOSE



Specially formulated hose designed to prevent "flavouring" the taste of your water. The hose is made with a blue EVA tube and clear cover. Meets AS/NZS 2070 standard. Suitable for Marine / Caravan use. Can be used with Garden hose 'click together type' fittings

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
12	18	1.0 MPa	145 psi	10 20 100 200#	P-SFR-012-***

Fitted assemblies available see page 48.

AIR BREATHING DIVERS / HOOKER HOSE



Yellow hose with food grade, non toxic PVC tube. Has excellent kink resistance and can be used for all air breathing applications. Meets AS/NZS 1716 and AS 2299 - 1979.

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
8	14.4	2.5 MPa	365 psi	100 300#	P-ABD-008-***
10	16.8	2.5 MPa	365 psi	100 300#	P-ABD-010-***

TUBING PRODUCTS



LDPE AIRSEEDER TUBING

Clear tubing designed for the transfer of seed products. UV Stabilised. Mirror Smooth for minimum flow loss.

ID (MM)	OD (MM)	COIL LENGTHS (METRES)	PART NO
25	33.0	30 100	T-LDP-025-***
32	37.0	30 100	T-LDP-032-***

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC PRESSURE HOSE



AIR / WATER

SAFETY YELLOW AIR / WATER



High quality Air/Water hose with strong durability and excellent flexibility. It's highly visible ribbed cover makes it an ideal choice for hard wearing industrial applications. Meets AS/NZS 2554 Class B requirements.

I.D (MM)	O.D (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
6	12	1.7 MPa	250 psi	20 100 300#	P-HSY-006-***
8	14	1.7 MPa	250 psi	20 100 300#	P-HSY-008-***
10	17	2.0 MPa	290 psi	20 100 200#	P-HSY-010-***
12.5	19	1.7 MPa	250 psi	20 100 200#	P-HSY-012-***
20	28	1.6 MPa	230 psi	20 100	P-PPY-020-***
25	33	1.6 MPa	230 psi	20 100	P-PPY-025-***
32	42	1.6 MPa	230 psi	20 40	P-HSY-032-***
38	50	1.6 MPa	230 psi	20 40	P-HSY-038-***
50	63	2.0 MPa	290 psi	20 40	P-HSY-050-***

4:1 Safety Factor on 6-12.5mm & 32-50mm 3:1 Safety Factor on 20 & 25mm

denotes the product is supplied on a plastic or wooden reel.

BEGA - WASH DOWN (Blue with White Stripe)



Premium washdown hose designed specifically for cold wash-down applications. It's distinctive construction using all virgin PVC compounds ensures unmatched performance and flexibility particularly at low temperatures. The smooth cover reduces the build up of dirt and grime making it the ideal dairy wash down hose. Suitable for Dairies, Paper Mills, Golf Courses & Nurseries. This product is metre marked to assist measurement. Temperature Range: -5°C - +60°C.

I.D (MM)	O.D (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	Weight Kg / mtr	PART NO.
20	28	1.0 MPa	145 psi	20, 50, 100	0.38	P-SBE-020-***
25	33	1.0 MPa	145 psi	20, 50, 60#, 100	0.51	P-SBE-025-***
32	42	1.0 MPa	145 psi	20 40 100	0.78	P-SBE-032-***
38	50	1.0 MPa	145 psi	20 40 100	0.97	P-SBE-038-***

TCW TURFCOLD WASHDOWN & IRRIGATION



This hose is manufactured with a white tube and white ribbed cover. For water transfer applications such as golf courses and small irrigators. The Irrigation Hose has excellent flexibility and kink resistance and a special blend of stabilisers provides optimum UV protection.

I.D (MM)	O.D (MM)	WORKING PRESSURE		COIL LENGTHS (METRE)	PART NO.
12.5	18	1.0 MPa	145 psi	20 100	P-TCW-012-***
19	26	1.0 MPa	145 psi	20 100	P-TCW-020-***
25	33	1.0 MPa	145 psi	20 100	P-TCW-025-***
32	42	1.0 MPa	145 psi	20 100	P-TCW-032-***

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC PRESSURE HOSE



AIR / WATER

HOT WASHDOWN - White



Heavy duty white hot wash hose ideal for dishwashers and washing machines. Designed for the conveyance of hot water up to 90°C whilst under pressure. Smooth non-marking white cover.

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
12.5	19	1.6 MPa	230 psi	20, 30, 100	P-HHW-012-***
20	29	1.4 MPa	200 psi	20, 100	P-HHW-020-***

FLINDERS - FIRE REEL



Black ribbed fire reel hose that meets AS/NZS 1221 standard. Heavy duty water transfer hose suitable for use on Fire Reels in industrial and domestic fire control systems, rural fire fighting pumps and general agricultural water transfer applications. Temperature Range: -5°C - +60°C

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	Weight Kg / mtr	PART NO.
19	26	1.0 MPa	145 psi	20, 36, 100	0.36	P-SFL-020-***
25	34	1.0 MPa	145 psi	20, 36, 100	0.55	P-SFL-025-***

*** 20mm available in Yellow. 33m & 100m coils. P-SFY-020-033 & P-SFY-020-100

LILAC RECLAIMED / GREY WATER



Distinctive Lilac covered hose manufactured & branded to meet the requirements for reclaimed / grey water use.

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
12.5	17	1.0 MPa	145 psi	20 100	P-SRW-012-***
19	25	1.0 MPa	145 psi	20 100	P-SRW-020-***
25	31	0.9 MPa	130 psi	20 100	P-SRW-025-***

LORNE - GARDEN Lime Green Translucent



Premium quality hose for general purpose water transfer in industrial and domestic applications. Manufactured with virgin PVC materials this product provides excellent flexibility even at low temperatures. Lorne carries a 5yr manufacturing warranty. Temperature Range: -5°C - +60°C

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
12.5	17	1.0 MPa	145 psi	20 35 100 200#	P-SLO-012-***
19	25	1.0 MPa	145 psi	20 35 100#	P-SLO-020-***
25	31	0.9 MPa	130 psi	20 35 100	P-SLO-025-***

denotes the product is supplied on a plastic or wooden reel.

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC PRESSURE HOSE



AIR / WATER

SUPERFLEX—10yr Warranty Green / Red Stripe

Manufactured to Australian Domestic Garden Hose Standard AS 2620. Excellent UV resistance. **10YR guarantee.** Hose is mtr marked to make it easier to cut to length



I.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	HEADER CARD	PART NO.
	Kpa	psi			
12	1200	175	18, 30, 100	On 18mtr Only	P-SFG-012-***
18	1200	175	18, 30, 100	On 18mtr Only	P-SFG-018-***



ACACIA - AIRLINE

Acacia Airline has been designed for air & water applications. It has good flexibility in cold temperature with excellent U.V resistance. The robust construction incorporating the high visibility blue & yellow cover and smooth inner tube offer excellent kink resistance. Manufactured to AS 2554 Class B.

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	Weight Kg / mtr	PART NO.
6	12	1.6 MPa	230 psi	20, 60#, 100, 300#	0.11	P-SCA-006-***
8	14.2	1.6 MPa	230 psi	20, 50#, 100, 300#	0.13	P-SCA-008-***
10	17.5	1.6 MPa	230 psi	20, 30, 40#, 100, 200#	0.18	P-SCA-010-***
12.5	19.5	1.6 MPa	230 psi	20, 30#, 100, 200#	0.19	P-SCA-012-***

denotes the product is supplied on a plastic or wooden reel.

FRAS AIR HOSE Coal Mining / Heavy Duty

FRAS rated PVC Hose, made from a lightweight, highly abrasive resistant polymer developed for use in underground coal mining. Conforms to AS 2660 and AS2554 class A.



I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
10	17	2.1 MPa	305 psi	20 100	P-FSA-010-***
12.5	22	2.1 MPa	305 psi	20 100	P-FSA-012-***
20	30	2.1 MPa	305 psi	20 100	P-FSA-020-***
25	34	2.1 Mpa	305 psi	20 33 100	P-FSA-025-***
25	34	3.45 Mpa	500 psi	20 33 100	P-FSA-025-***
32	44	2.1 Mpa	305 psi	20 100	P-FSA-032-***
38	50	2.1 MPa	305 psi	20 40	P-FSA-038-***
50	63	2.1 MPa	305 psi	20 40	P-FSA-050-***

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC PRESSURE HOSE



PETROLEUM



PR PETROL RESISTANT

Petrol resistant hose that has a black cover with a red tube. All sizes come with two copper anti-static wires as standard. Suitable for use on Mini Tanker Hose Reels, Farm Bulk Holding tanks etc.

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
25	33	1.4 MPa	200 psi	20 100	P-HPR-025-***
32	42	1.4 MPa	200 psi	20 60 100	P-HPR-032-***
38	50	1.1 MPa	160 psi	20 40 60	P-HPR-038-***

DRUM PUMP II



Drum Pump hose has a high resistance to most common petroleum products. Most suited to low pressure or gravity fed delivery of diesel and kerosene from farm storage. (other sizes available on request)

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
25	31	0.9 MPa	130 psi	3, 20, 100	P-DPH-025-***

CHILLMASTER ANTI-STATIC DRUM PUMP HOSE



Black Fuel resistant hose with excellent cold weather flexibility. Specially formulated compounds give this hose a high resistance to common petroleum products. Has two antistatic wires for earthing. Premium hose for the most demanding applications. (other sizes available on request)

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
25	33	1.0 MPa	145 psi	20 100	P-CHM-025-***

LP GAS HOSE



LP Gas hose for domestic appliances. Suitable for conveying L.P. Gas. Conforms to AS/NZS1869 Class A & C

I.D. (MM)	O.D. (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO.
5	12.5	2.7 MPa	385 psi	100	P-LPG-005-***
6	13	2.7 MPa	385 psi	100	P-LPG-006-***
8	15	2.7 MPa	385 psi	100	P-LPG-008-***

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

TUBING PRODUCTS



FOOD / MULTIPURPOSE



CLEAR VINYL TUBING

Suitable for food and beverage lines operating at low pressures, general purpose low pressure delivery lines, light syphon lines, cable protection, drainage lines etc. Conforms to AS/NZS 2070 standard. Manufactured from premium quality PHENOL FREE materials. NOT SUITABLE FOR ETHANOL

I.D. (MM)	WALL THICKNESS (MM)	COIL LENGTHS (METRES)	PART NO
3	1.0	30, 200#	T-CVT-003-030
4	1.0	30, 150#	T-CVT-004-030
5	1.5	30, 100#	T-CVT-005-030
6	1.5	30, 100#	T-CVT-006-030
8	1.5	30, 100#	T-CVT-008-030
10	1.5	30, 75#	T-CVT-010-030
12.5	1.5	30, 50#	T-CVT-012-030
16	1.5	30, 30#	T-CVT-016-030
20	2.0	30	T-CVT-020-030
25	2.5	30	T-CVT-025-030
32	3.0	10, 30	T-CVT-032-030
38	3.5	10, 15, 30	T-CVT-038-***
50	4.0	15 30	T-CVT-050-***

denotes the product is supplied on a plastic or wooden reel.

EVA - BEVERAGE TUBE



Non Toxic Beverage tube suitable for beer dispensing and drinking water conveyance.

ID (MM)	WALL THICKNESS (MM)	COIL LENGTHS (METRES)	PART NO
4	1.5	100	T-BVT-004-100
5	1.5	100	T-BVT-005-100
6	2.0	100	T-BVT-006-100
8	2.0	100	T-BVT-008-100
10	2.5	100	T-BVT-010-100
12.7	2.5	100	T-BVT-012-100

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC SUCTION HOSE



WATER

SILVERWATER GREY SUCTION



For conveying water and other liquids and light granular materials in agriculture and industrial applications. Super flexible product ensuring optimum performance.
Temperature Range: -5°C - +60°C

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	PRESSURE (PSI)	MIN BEND RADIUS mm	COIL LENGTHS (METRES)	WEIGHT Kg/mtr	PART NO.
25	31.9	-624	130	120	20	0.40	Q-SSW-025-***
32	39.4	-624	116	150	20	0.60	Q-SSW-032-***
38	46.1	-624	102	200	20, 30	0.72	Q-SSW-038-***
45	52.6	-624	102	250	20	0.86	Q-SSW-045-***
50	60.2	-624	87	300	20, 30	1.08	Q-SSW-050-***
63	74.4	-624	87	400	20	1.55	Q-SSW-063-***
76	89.6	-624	73	450	20	2.30	Q-SSW-075-***
102	116	-624	58	600	20	3.20	Q-SSW-100-***
127	141	-600	60	800	6, 20	3.80	Q-SSW-125-***
140	152	-600	45	950	20	4.30	Q-SSW-140-***
152	170	-600	45	1100	20	5.55	Q-SSW-150-***

THOMPSON TANK TRANSFER HOSE



The Thompson Tank hose is a food contact non-toxic water transfer hose designed to be used as a low pressure transfer line between water tank installations. It conforms with AS/NZ 2070 for food contact. It's distinctive olive colour sets it apart from standard water transfer hoses. Temperature Range: -5°C - +60°C

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	PRESSURE (PSI)	MIN BEND RADIUS mm	COIL (METRES)	WEIGHT Kg/mtr	PART NO.
25	31.9	-550	130	120	20	0.40	Q-STH-025-***

FOOD / BEVERAGE

Plutone PR

Plutone PR hose is a food contact non-toxic water transfer hose designed to be used as a pressure or suction line in Food / beverage Applications. It conforms with CEE 90/128 Class ABC. It has a Red Stripe with Clear Braiding & Suction Wire.
Temperature Range: -10°C - +60°C



I.D. (MM)	O.D. (MM)	VACUUM (Bar)	PRESSURE (PSI)	MIN BEND RADIUS mm	COIL (METRES)	WEIGHT Kg/mtr	PART NO.
25	35.0	-1.0	185	75	30	0.64	Q-HSP-025-***
38	49.0	-1.0	142	110	30	1.01	Q-HSP-038-***
50	63.0	-1.0	114	150	30	1.60	Q-HSP-050-***
76	91.0	-1.0	85	228	30	2.69	Q-HSP-075-***

All dimensions are nominal. Products may vary slightly to those pictured




Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



FOOD GRADE



KOSCIUSZKO

CLEAR - STEEL HELIX - FOOD GRADE (PLUTONE A / HELISTEEL)

Suitable for applications requiring continuous bending and flexing, or where a clear and /or heavy duty hose is required, including food contact, beverages. Can be used for oils and pesticides (boom sprayers)
 Conforms to AS/NZ 2070 for use with food stuffs - liquids, dry and alcohol.

I.D. mm	O.D. mm	VACUUM (mm/Hg)	PRESSURE PSI	COIL LENGTHS M	PART NO.
6	12	-699	100	30 60	Q-SKO-006-***
8	14	-699	100	30 60	Q-SKO-008-***
10	16	-625	100	30 60	Q-SKO-010-***
12	18	-625	85	30 60	Q-SKO-012-***
16	22	-625	85	30 60	Q-SKO-016-***
19	27	-625	71	30 60	Q-SKO-020-***
25	33	-625	71	30	Q-SKO-025-***
32	41	-625	57	30	Q-SKO-032-***
38	47	-625	57	30	Q-SKO-038-***
50	60	-588	57	30	Q-SKO-050-***
63	76	-588	51	30	Q-SKO-063-***
76	85	-515	51	30	Q-SKO-075-***
102	115	-515	34	30	Q-SKO-100-***
127	141	-662	30	20	Q-SKO-125-***
152	170	-662	25	20	Q-SKO-150-***

Larger lengths available up to 200m on request. - Manufactured to order.

FOOD CONTACT CLEAR / WHITE HELIX



For non-toxic applications. Meets AS/NZS 2070. For use as a milk tanker suction and delivery hose.

I.D. mm	O.D. mm	VACUUM (mm/Hg)	RATING Kpa	COIL LENGTHS m	PART NO.
25	32	-720	-80	20	Q-MFX-025-***
32	41	-720	-80	20	Q-MFX-032-***
38	46	-720	-80	20	Q-MFX-038-***
50	59	-675	-80	20	Q-MFX-050-***
64	75	-675	-80	20	Q-MFX-063-***
76	85	-675	-80	20	Q-MFX-075-***
100	115	-675	-80	30.5	Q-MFX-100-030

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC SUCTION HOSE



FOOD GRADE

RIVERINA (PHENOL FREE) CLEAR / RED HELIX



Riverina suction hose is manufactured from a heavy duty PVC compound with a rigid PVC helix. Suitable for the suction and discharge of wine, spirits and fruit juices up to 28 proof. Conforming to AS/NZ 2070 - 1999, plastic materials for food contact use. Smooth inner bore enables ease of cleaning and minimises bacteria build up. Manufactured from premium quality PHENOL FREE polymer.
Temperature Range: -5°C - +60°C

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	PRESSURE (PSI)	MIN BEND RADIUS mm	COIL LENGTHS (METRES)	WEIGHT Kg/mtr	PART NO.
25	31.9	-624	130	120	20	0.40	Q-SRI-025-***
32	39.4	-624	116	150	20	0.60	Q-SRI-032-***
38	46.1	-624	102	200	20	0.72	Q-SRI-038-***
50	60.2	-624	87	300	20	1.08	Q-SRI-050-***
63	74.4	-624	87	400	20	1.55	Q-SRI-063-***
76	89.6	-624	73	450	20	2.30	Q-SRI-075-***
102	116	-624	58	600	20	3.20	Q-SRI-100-***

PVC SUCTION HOSE

OIL / PETROL BASED

BASS BLUE OIL SUCTION HOSE



The Bass oil suction hose has been designed with extreme flexibility and an excellent resistance against mild chemicals and petroleum based products making it the product of choice for liquid waste suction and transfer. The nitrile blend used in the manufacture of this hose assists flexibility and manual handling, making ideal for use in cold climates.
Suitable for use on boom sprayers and spray tanks for pesticide transfer.
Temperature Range: -5°C - +60°C

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	PRESSURE (PSI)	MIN BEND RADIUS mm	COIL LENGTHS (METRES)	WEIGHT Kg/mtr	PART NO.
25	31.9	-624	130	120	20	0.40	Q-SBA-025-***
32	39.4	-624	116	150	20	0.60	Q-SBA-032-***
38	46.1	-624	102	200	20	0.72	Q-SBA-038-***
50	60.2	-624	87	300	20	1.08	Q-SBA-050-***
63	74.4	-624	87	400	20	1.55	Q-SBA-063-***
76	89.6	-624	73	450	20	2.30	Q-SBA-075-***
102	116	-624	58	600	20	3.20	Q-SBA-100-***

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC HOSE
LAYFLAT HOSE
RUBBER HOSE
ASSEMBLIES
AUTO HOSE
DUCTING
FITTINGS
NOZZLES
VALVES
CAMLOCKS
CLAMPS
REELS
PNEUMATICS
HYDRAULICS
PIPE SYSTEMS
RUBBER PRODUCTS
TRANSMISSION
TECH INFO

PVC SUCTION HOSE



MATERIAL HANDLING



BASS BLACK

Flexible Black Suction Hose suitable for suction and low pressure delivery of water, mild chemicals and petroleum based products. Typically used on boom sprayers & spray tanks for pesticides transfer. Also suitable for oils etc in sullage pick up applications.

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	PRESSURE (PSI)	COIL LENGTHS (METRES)	PART NO.
25	32	-624	130	20	Q-SBA-B-025-***
32	39	-624	116	20	Q-SBA-B-032-***
38	46	-624	102	20	Q-SBA-B-038-***
50	60	-624	87	20	Q-SBA-B-050-***
76	89	-624	73	20	Q-SBA-B-075-***



TIGERTAIL

For conveying petroleum products and derivatives, lubricating oils and various chemicals and sullage.

I.D. mm	O.D. mm	VACUUM (mmHg)	PRESSURE PSI	COIL LENGTHS m	PART NO.
50	61	-600	100	20	Q-TGR-050-***
63	76	-600	100	20	Q-TGR-063-***
76	90	-525	85	20	Q-TGR-076-***
100	118	-525	75	20	Q-TGR-100-***
125	143	-450	75	20	Q-TGR-125-***
150	167	-450	75	20	Q-TGR-150-***
203	222	-375	60	20	Q-TGR-200-***

MARINE SANITATION HOSE - WHITE

For conveying Sullage and Sanitary waste in boats, caravans etc.
White Smooth Bore & Cover



I.D. mm	O.D. mm	VACUUM (mmHg)	PRESSURE PSI	COIL LENGTHS m	PART NO.
20	28	-525	120	20	Q-HES-020-***
25	32	-525	120	20	Q-HES-025-***
38	45	-525	90	20	Q-HES-038-***

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC SUCTION HOSE



LPG VENT / AIR SEEDER



MAQUARIE MARINE BILGE PUMP - LPG VENT

Designed to meet the needs of a variety of applications. Smooth sealed inner bore. Raised helix increases flexibility. Popular on marine bilge pumps and marine cable protection. This product is also used as a vent hose in automotive LPG installations.

I.D. mm	O.D. mm	VACUUM (mm/Hg)	RATING Kpa	COIL LENGTHS m	PART NO.
20	25	-350	-46	20	Q-SMA-020-***
25	31	-350	-46	20	Q-SMA-025-***
28	34	-350	-46	20	Q-SMA-028-***
32	39	-350	-46	20	Q-SMA-032-***
38	45	-350	-46	20	Q-SMA-038-***
52	59	-350	-46	20	Q-SMA-050-***

FLEXI-FLO AIRSEEDER

Black, super tough flexible Airseeder and general purpose hose with superior UV resistance.



I.D. (mm)	O.D. (mm)	COIL LENGTHS (METRES)	PART NO.
12	19	20	Q-FLE-012-020
20	26	20	Q-FLE-020-020
25	33	20	Q-FLE-025-020
28	35	20	Q-FLE-028-020
30.5	39	20	Q-FLE-030-020
31.5	41.5	20	Q-FLE-031-020
32	43	20	Q-FLE-032-020
33.5	44	20	Q-FLE-033-020
35	44	20	Q-FLE-035-020
38	47	20	Q-FLE-038-020
44	55	20	Q-FLE-045-020
50	63	20	Q-FLE-050-020
63	77	20	Q-FLE-063-020
76	93	20	Q-FLE-075-020
102	116	20	Q-FLE-100-020



All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC SUCTION HOSE



AIR SEEDER

SUNRAYSIA (CLEAR / BLACK) AIR SEEDER HOSE



The Sunraysia air seeder hose is designed to suit tough Australian air seeder applications. Manufactured from a clear flexible PVC allowing accurate blockage detection, it's smooth bore helps to reduce friction loss and seed damage. Available in a wide range of sizes to suit primary, secondary and tertiary seed delivery lines.

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	PRESSURE (PSI)	MIN BEND RADIUS mm	COIL LENGTHS (METRES)	WEIGHT Kg/mtr	PART NO.
25	31.9	-624	130	120	20	0.40	Q-SSU-025-***
32	39.4	-624	116	150	20	0.60	Q-SSU-032-***
38	46.1	-624	102	200	20	0.72	Q-SSU-038-***
44	52.6	-624	87	250	20	0.86	Q-SSU-045***
50	60.2	-624	87	300	20	1.08	Q-SSU-050-***
63	74.4	-624	87	400	20	1.55	Q-SSU-063-***
76	89.6	-624	73	450	20	2.30	Q-SSU-075-***

CLEAR / WHITE SPIRAL AIRSEEDER HOSE



Used as an "Air Seeder" hose and other applications where materials being conveyed need to be seen.

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	RATING (Kpa)	COIL LENGTHS (METRES)	PART NO.
25	33	-600	-80	20	Q-SFX-025-***
32	38	-600	-80	20	Q-SFX-032-***
38	46	-600	-80	20	Q-SFX-038-***
45	53	-600	-80	20	Q-SFX-045-***
50	59	-600	-80	20	Q-SFX-050-***
63	72	-600	-80	20	Q-SFX-063-***
76	86	-600	-80	20	Q-SFX-075-***

SPLIT CORRUGATED TUBE BLACK

Polypropylene cable protection tube, split longitudinally to allow cables etc to be freely placed inside.



I.D. (MM)	VACUUM (mm/Hg)	RATING (Kpa)	COIL LENGTHS (METRES)	PART NO.
7	N/A	N/A	10mtr bag	E-SCT-007-010
10	N/A	N/A	10mtr bag	E-SCT-010-010
13	N/A	N/A	10mtr bag	E-SCT-013-010
16	N/A	N/A	10mtr bag	E-SCT-016-010
20	N/A	N/A	10mtr bag	E-SCT-020-010

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC SUCTION HOSE



GREY WATER PRODUCTS

WASHING MACHINE DRAIN HOSE EXTENSION C/W CUFF

Corrugated 10mtr length of black hose for connections to the washing machine or as an extension to the existing drain hose. Comes complete with cuffs for ease of connection.



I.D. MM	O.D. MM	VACUUM	RATING	COIL LENGTHS M	PART NO.
22	28	n/a	n/a	10	Q-WMH-022-010F

SPARE CUFF FOR EXTENSION HOSES

I.D. (MM)		PART NO.
22	EACH	Q-WMH-022CUF



PVC SUCTION HOSE

CARPET CLEANING



G-VAC VACUUM CLEANER HOSE

This hose was developed specifically for use with steam cleaning equipment. Available in Grey or orange. Extremely flexible with a smooth exterior and interior ensures tangle free operation.

I.D. mm	O.D. mm	VACUUM (mm/Hg)	RATING Kpa	COIL LENGTHS m	PART NO.
38	39	-600	-80	15	Q-GVA-038-015
50	61	-600	-80	15	Q-GVA-050-015

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PVC SUCTION HOSE



POOL & SPA

BLO-FLEX BLOW MOULDED White Segmented



Australian made blow molded hose. Segmented in 1000mm Lengths.

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	RATING (Kpa)	COIL LENGTHS (M)	PART NO.
32	40	n/a	n/a	50	E-BLO-032-050
38	47	n/a	n/a	50	E-BLO-038-050

STA-FLEX - STANDARD POOL HOSE Blue 2yr Warranty



Quality hose has a two year warranty and is a tough durable product that has excellent flexibility. (Cuffs & Joiners available)

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	RATING (Kpa)	COIL LENGTHS (M)	PART NO.
32	40	-600	-80	50	E-STA-032-050
38	47	-600	-80	30	E-STA-038-030

SPA SUCTION HOSE - White



Flexible Suction Discharge Hose for flexible plumbing lines in spa's. This tough hose is designed specifically for hard wearing applications. For use with PVC fittings and Cement.

I.D. (MM)	O.D. (MM)	VACUUM (mm/Hg)	RATING (Kpa)	COIL LENGTHS (M)	PART NO.
12	21	-600	-80	15	E-SSF-012-015
20	27	-600	-80	15	E-SSF-020-015
25	33.5	-600	-80	15	E-SSF-025-015
38	48	-600	-80	15 30	E-SSF-038-***
50	60	-600	-80	15 30	E-SSF-050-***
76	89	-600	-80	15	E-SSF-075-015

SPA TUBE (CLEAR)



Thick wall Clear tubing designed for Australian spa bath and Pool applications.

ID (mm)	OD (mm)	Coil Lengths (METRES)	Part No
9.0	14.0	100	E-CVT-009-100
19.0	25.0	50	E-CVT-019-050

All dimensions are nominal. Products may vary slightly to those pictured



Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE