

SILVERWATER



SILVERWATER - (Q-SSW) Grey Suction Hose

The FHS Silverwater Grey Suction Hose is manufactured from heavy duty flexible PVC. This product is suitable for the suction and discharge of liquids and granular materials in pumping applications. It is manufactured with a smooth inner bore to reduce friction loss, this combined with its abrasion resistant qualities also makes it suitable for air seeder applications.

FEATURES:

- Excellent Flexibility
- Smooth Inner Bore
- High Abrasion resistance
- UV Stabilized
- Temperature Range - (-5°C to + 60°C)
- Compound - Flexible PVC / Rigid PVC Helix
- Working pressures tested at 20°C.

APPLICATIONS:

- Primary, Secondary & Tertiary air seeder lines.
- General Purpose water, liquid and granular suction and low pressure delivery.



PVC SUCTION HOSE

Nominal ID	Nominal OD	Working Pressure	Vacuum Rating	Minimum Bend Radius	Weight	Length
mm	mm	psi	mm Hg	mm	kg/mtr	m
25	31.9	130	624	120	0.40	20
32	39.4	116	624	150	0.60	20
38	46.1	102	624	200	0.72	20
44	52.6	102	624	250	0.86	20
50	60.2	87	624	300	1.08	20
63	74.4	87	624	400	1.55	20
76	89.6	73	624	450	2.30	10, 20
102	116	58	624	600	3.20	10, 20

All dimensions are nominal

MADE IN AUSTRALIA



**FLUID HANDLING
SOLUTIONS**

Ph: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

"guaranteed to deliver"

MELBOURNE - SYDNEY - NEWCASTLE

